

ROUES COMPLÈTES - VITESSE ROUTIÈRE

WHEELS AND TYRES - HIGH SPEED



RÉF.	DIMENSION	Charge maxi/ Essieu (kg)		* Pression bars	Diam. x Larg. mm	Perçage	Déport mm	Poids kg
		solo	tandem					
1403079	145/70 R 13	690		2.5	534 x 150	4x130	20	11
1403080	155/70 R 13	774		2.5	548 x 157	4x130	20	11
1403081	165/70 R 13	874		2.5	562 x 170	4x130	20	12
1403082	175/70 R 13	950		2.5	576 x 177	4x130	20	13
1403083	185/70 R 13	1060		2.5	590 x 189	4x130	20	14
1403073	155/70 R 12 C	1300	1180	5	523 x 157	4x130	0	13
1403101	155/70 R 12 C	1800	1600	6.5	523 x 157	5x140	0	13
1403128-30	155/70 R 12 C	1800	1600	6.5	523 x 157	5x112	30	13
1403270	195/55 R 10	1320		6.5	468x201	4x130	0	14
1403271	195/55 R 10	1500		6.5	468x201	5x140	0	14
1403196	195/50 R 13 C 8PR	1800	1700	6.5	526 x 201	5x112	30	18
1403188	195/50 R 13 C 8PR	1800	1700	6.5	526 x 201	5x140	30	18
1403084	185 R 14 C 8PR	1700		4.5	650 x 188	4x130	20	21
1403086	185 R 14 C 8PR	1700		4.5	650 x 188	5x140	0	21
1403141	195 R 14 C 8PR	1800		4.5	666 x 198	5x140	0	22
1403142	195 R 14 C 8PR	1800		4.5	666 x 198	5x112	30	22
1403241	215 R 14 C 8PR	2100		4.5	700 x 218	5x140	0	24
1403162	225/75 R 16 C	2900	2720	5.75	744 x 223	6x205	0	29.5

* Pressions à titre indicatif, se reporter aux inscriptions sur le flanc du pneu (100kPa = 1bar = 14.5psi)