

CONTENTS

COMPLETE WHEELS



COMPLETE WHEELS - HIGH SPEED

4

COMPLETE WHEELS - HIGH SPEED



REF.	DIMENSION	Maximum load / Axles (kg)		(1) Pressure bars	(2) Diam x Width mm	Drilling	Offset mm	Weight kg
		solo	tandem					
1403079	145/70 R13	690	-	2.5	534x150	4x130	20	11
1403080	155/70 R13	774	-	2.5	548x157	4x130	20	11
1403081	165/70 R13	874	-	2.5	562x170	4x130	20	12
1403082	175/70 R13	950	-	2.5	576x177	4x130	20	13
1403083	185/70 R13	1060	-	2.5	590x189	4x130	20	14
1403073	155/70 R12 C	1300	1180	5	523x157	4x130	0	13
1403101	155/70 R12 C	1800	1600	6.5	523x157	5x140	0	13
1403128-30	155/70 R12 C	1800	1600	6.5	523x157	5x112	30	13
1403270	195/55 R10	1320	-	6.5	468x201	4x130	0	14
1403271	195/55 R10	1500	-	6.5	468x201	5x140	0	14
1403196	195/50 R13 C	1800	1700	6.5	526x201	5x112	30	18
1403188	195/50 R13 C	1800	1700	6.5	526x201	5x140	30	18
1403044	165 R14 C	1460	-	4.5	623x166	4x130	20	20
1403156	165 R14 C	1460	-	4.5	623x166	5x140	0	20
1403084	185 R14 C	1700	-	4.5	650x188	4x130	20	21
1403086	185 R14 C	1700	-	4.5	650x188	5x140	0	21
1403141	195 R14 C	1800	-	4.5	666x198	5x140	0	22
1403142	195 R14 C	1800	-	4.5	666x198	5x112	30	22
1403241	215 R14 C	2100	-	4.5	700x218	5x140	0	24
1403162	225/75 R16 C	2900	2720	5.75	744x223	6x205	0	29.5
1403108	215/75 R17.5	4360	4120	8.6	767x211	6x205	0	50

(1) Pressures are indicative; refer to the markings on the tire sidewall (100 kPa = 1 bar = 14.5 psi)

(2) Maximum theoretical dimensions